



Clean & Seal NF-25

Lo Foam Aluminum Cleaner & Inhibitor

Clean & Seal NF-25 is a high-performance degreaser for aluminum and other non-ferrous and ferrous metals. An ideal choice for highly machined surface cleanliness.

NF-25 is an advanced formula providing superior cleaning of greases and lubes which are resistant. NF-25 provides extended corrosion protection to steel & nonferrous metals. 3-6 Months of indoor protection.

NF-25 has low alkaline pH which provides a safer product for employee use and handling. May also be used in vibratory, immersion or wand applications.

Features & Benefits

- Rapid soil penetration and lifting of contaminants.
- Film free rinsing without residue.
- Mild to skin.
- Non caustic.
- Lifts grease, oils and lubricants from surfaces and recesses of machined parts and other difficult substrates.
- Non-phosphated and biodegradable.
- Low use level
- Economical
- Concentrated
- Biodegradable
- Neutral pH
- Ease of disposal
- Provides bright finish on aluminum without etching.

Physical Data

pH	8.5
Product Type	Liquid
Spec. Gravity	1.02
lbs./gal.	8.51
Foam, 0 = Low, 9 = High	1
Shelf-Life Years	10 years



Freeze Information	Not damaged by freezing.
--------------------	--------------------------

Typical Processing

1. Dilute with water: use at 2 - 10% by volume (5% typical)
 - a. Spray on, time= 1/2-up to 10 minutes. (as required)
 - b. Temp: as required to aid in drying & soil removal (72 - 170 f.)
2. Power Wash Cleaning = 1 - 5 minutes soak cleaning= 5-10 minutes typical
3. Vibe cleaning = 10-30 minutes typical.
4. Temperature: as required, (room temp.) 80 f. to 180 degrees.
5. All types of media can be used when processing with NF-25.

Packaging

Container Type	Poly
Net Units	467
Tare Wt.	25 lb.
Gross Wt.	492
DOT_Name	Not regulated by D.O.T.
DOT Hazard	Not regulated
Tarriff ID	

Use Parameters

Concentration Range	1/2-20%
Temperature Range	Ambient 80- 200 F.
Time Range	AS required by job.
Agitation	Recommended.

Waste Disposal

Remove oils and grease.

Holding Tank Materials of Construction

Steel, stainless, or poly.

Other Information

It is important that the OSHA DATA, "Material Safety Data Sheet" be carefully read and reviewed



with the users of this product. OSHA data is required to be posted in the work area by law.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.